

APLINK MR1400


Full Graphic performance high resolution inkjet printer.

Aplink MR Series high resolution inkjet printer developed for printing immediately any type of high quality barcode upon cardboard boxes. Fulfilling GS1 (EAN International) barcode regulation, it's also able to print 180 x 180 dpi images, reaching highest printing heights in the market.

It uses Windows TM true type fonts. Easy to use WYSIWYG terminal, USB and Ethernet connectivity (integrated) RF Wireless (optional).

One of its outstanding advantages among other is the capacity to print up to 140 mm. message printing height and perform the identification, coding and even decoration of the products in real time in the same production line. Its easy access to external database makes possible obtaining data for printing, It can be connected to a PLC providing an easy selection of the messages that must be printed.

Multi-product and easy maintenance, capable to print on tops and sides up to 30 mts/min.











IMPRESION POR CHORRO DE TINTA

UBS

United Barcode Systems


GENERAL DESCRIPTION High Resolution Inkjet Printing System POWER SUPPLY 110 / 220 V 50-60 Hz. HEIGHT min. 810 mm. (31,8 in) max. 1.580 mm. (62,2 in.) TEMPERATURE from + 10 °C (50 °F) to + 50 °C (122 °F) HUMIDITY from 5% to 85% non condensed	TECHNICAL SPECIFICATIONS	S
HEIGHT min. 810 mm. (31,8 in) max. 1.580 mm. (62,2 in.) TEMPERATURE from + 10 °C (50 °F) to + 50 °C (122 °F)	GENERAL DESCRIPTION	High Resolution Inkjet Printing System
TEMPERATURE from + 10 °C (50 °F) to + 50 °C (122 °F)	POWER SUPPLY	110 / 220 V 50-60 Hz.
	HEIGHT	min. 810 mm. (31,8 in) max. 1.580 mm. (62,2 in.)
HUMIDITY from 5% to 85% non condensed	TEMPERATURE	from + 10 °C (50 °F) to + 50 °C (122 °F)
	HUMIDITY	from 5% to 85% non condensed

CONSUMABLE	
INKS	Oil based
COLOURS	Black, Red, Blue and Yellow. Other under request.
PACKING	1 lt. lnk Bottle
PRINTING MATERIALS	All types of porous surface

PRINTING FEATURES	
PRINTING HEIGHT	Up to 140 mm. (5,5 in.)
RESOLUTION	180 x 180 dpi.
PRINTING SPEED	Up to 30 meters / minute
BARCODES	DUN-14, EAN-8, EAN-13, CODE 19, CODE 128, 2/5 INDUSTRIAL, DATAMATRIX
FIXED OR VARIABLE	Formulas, counters, dates, free fields. Uses Windows TM and Truetype TM fonts
GRAPHICS	Logos and all type of images
OPTIONS	Intelligent Guide, Special heights support encoder, Printhead protection, low temperatures option.
INTERFACE	Digital touchscreen display.

APLINK CONNECTIVITY

















We reserve the right to amend the design and/or specifications of our products without notice.





Labeling, Coding and Marking Solutions United Barcode Systems